

# HIGH SPEED GREASE 2

### DESCRIPTION

**HIGH SPEED GREASE 2** is a premium quality synthetic base oil grease thickened with a complex lithium soap. Our unique blending technology integrated with a synthetic low viscosity base oil allow this grease to be extremely effective in extremely high-speed ball & roller bearing applications.

### APPLICATIONS

- Printing cylinders
- Machine tools: CNC Lathes, Grinders & Milling machines
- Textile spinning spindles
- Electric motors
- Instrument & control equipment
- Fan bearings

### FEATURES AND BENEFITS

- Wide temp range -30°C to + 130°C
- Low friction torque
- Good extreme pressure properties
- Reduces noise
- Oxidation and corrosion inhibited
- Extends lubrication intervals



Pack Sizes: 400g, 12.5kg, 18kg, 50kg & 185kg



Property	Test Method	Result
Appearance	Visual	Buttery brown grease
NLGI no.	IP-50 – ASTM D217	2
Base oil type	N/A	Synthetic
Base Oil Viscosity @ 40°C	IP 71	11 cSt
Base Oil Viscosity @ 100°C	IP 71	4 cSt
Thickener	N/A	Lithium complex soap
DnM Factor	N/A	1,250,000
Temp range	N/A	-60°C to + 130°C
4-Ball weld load	IP 239 – ASTM D2596	200 kgs

This data is supplied in good faith but without warranty. We do not assume responsibility and expressly disclaim any liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product. This Data Sheet was prepared solely for the product stated and should not be used for any other product.

Product Code: ML-11041