



## Technical Data Sheet

### Indu-Tek Long-Life CS2 Grease

Heavy Duty, Superior Performance, High Temperature, Water Resistant  
Calcium Sulphonate Complex Grease

**Long-Life CS2 Grease** is a superior quality multi-purpose grease, formulated to meet the requirement of the most extreme industrial applications and diverse temperatures.

**Long-Life CS2 Grease** is suitable for all types of Anti-Friction, Plain Bearings and Sliding Surfaces.

#### Features and Benefits: -

- Extreme Load Bearing Capacity >700kg's weld load
- Excellent Operating temp range -30°C - 180°C
- Completely water resistant – no loss of consistency even when saturated
- Excellent Anti-Oxidation & Anti-Corrosion properties
- Does not contain lead, or other metallic substrates harmful to the Environment or Human Health
- Long-Life application – extends relubrication periods

#### Directions for Use: -

**Long-Life CS2 Grease** can be applied by hand, or by using a standard grease gun or via a centralised lubrication system compatible for pumping an NLGI No.2 grease.

As with all greases used for the first-time check compatibility with the grease applied previously and if necessary purge the bearings prior to application.

#### Packaging: -

**Long-Life CS2 Grease** is available in 400gram, 12.5kg 18kg, 50kg and 180kg drums.

Part Number: ML-11545

This data is supplied in good faith but without warranty. We do not assume responsibility and expressly disclaim any liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product. This Data Sheet was prepared solely for the product stated and should not be used for any other product.



A British Lubricant Company

Mako-Lube Lubricants is a registered  
trademark & brand of Brit-Lube Limited

Brit-Lube Ltd, Manchester, UK. Tel: +44 (0)161 777 9970  
www.mako-lube.com info@mako-lube.com



## Specific Data

### Indu-Tek Long-Life CS2 Grease

Heavy Duty, Superior Performance, High Temperature, Water Resistant  
Calcium Sulphonate Complex Grease

#### Typical Characteristics and properties

|                            |   |                              |
|----------------------------|---|------------------------------|
| Appearance                 | - | Smooth buttery grease        |
| Colour                     | - | Brown                        |
| NLGI classification (IP50) | - | 2                            |
| Worked penetration (IP50)  | - | 250 to 295                   |
| Base oil Viscosity         | - | 460 cst                      |
| Water wash out             | - | < 1%                         |
| Dropping point             | - | >280°C                       |
| Timken OK Load (IP236)     | - | 60 lbs                       |
| Thickener                  | - | Calcium sulphonate complex   |
| Working temperature range  | - | -30°C to 180°C short periods |

This data is supplied in good faith but without warranty. We do not assume responsibility and expressly disclaim any liability for loss, damage or expense arising out of or in any way connected with handling, storage, use or disposal of this product. This Data Sheet was prepared solely for the product stated and should not be used for any other product.



A British Lubricant Company

Mako-Lube Lubricants is a registered  
trademark & brand of Brit-Lube Limited

Brit-Lube Ltd, Manchester, UK. Tel: +44 (0)161 777 9970  
[www.mako-lube.com](http://www.mako-lube.com) [info@mako-lube.com](mailto:info@mako-lube.com)